



THE Q

All-in-One Hydration Station

Instant Boiling, Chilled & Sparkling Water at Your Fingertips



BOILING



CHILLED



SPARKLING



The Q

Introducing The Q, a compact smart tap system that effortlessly dispenses instant boiling, chilled, and sparkling water. Designed as an additional faucet, it features a sleek brushed stainless steel tap, a versatile control pad, and a space-saving under-sink unit—perfect for homes and light-use shared spaces.

Key Features:



Sustainable Sparkling

Delivers 100L (~500 glasses) of sparkling water from a single 1L CO₂ cylinder. Includes two refillable cylinders.



Smart Control Pad

Modular pad with real-time temperature display. Place anywhere around the sink.



Temperature Controlled

Instant boiling with adjustable temperatures (80°C / 176°F or 92-95°C / 198-203°F), perfectly chilled (2-6°C / 36-43°F), and refreshing sparkling water.



Eco Mode

Programmable boiler downtime (8, 12, or 24 hours) to conserve energy when not in use.



Elegant Design

Brushed 304 stainless steel faucet designed to complement any kitchen aesthetic.



Safety First

Child safety lock, automatic shutoff, and leak detection tray included.



Space-Saving

Compact under-sink unit fits in spaces as small as 450mm (18"). All-in-one efficiency.



Easy Installation

Compatible with external RO systems. Water-cooled—no ventilation required.





Specifications

Under-sink Unit



Voltage:	110V or 220V (Type B, F, G plugs)
Power:	1,240 W
Inlet Pressure:	1.5–4 bar (22–57 psi)
Dimensions:	290 × 420 × 440 mm (W11.4 × D16.5 × H17.3")
Weight:	24 kg (53 lb)
Dispense Rate:	1.5 LPM (0.4 GPM) all modes
Safety:	Leak tray with auto-detection shutoff

Faucet



Material:	304 stainless steel, brushed finish
Dimensions:	42 × 252 × 380 mm (W1.7 × D9.9 × H15.0")
Spout Height:	230 mm (9")
Installation:	1.2m tubing to under-sink unit

Control Pad



Dimensions:	40.5 × 186 × 18 mm (W1.6 × D7.3 × H0.7")
Display:	Water temperature & heating status
Settings:	Hot water: 95°C or 80°C with safety lock

CO₂ Cylinder & Regulator



Includes:	Includes: 2× 1L / 600g refillable cylinders
Certifications:	Certifications: PI (EU/international) & DOT (US)
Regulator:	Regulator: Adjustable 2–4 bar output



Contact us today to learn more or place your order!

www.quatreau.com